



EH MINI P LED SPEED

Code no. 3001254

- // Connection to Hensel Porty generators only
- // Short flash duration t 0.5: 1/3,200 s - 1/8,100 s (Porty L 600),
1/1,800 s - 1/5,200 s (Porty L 1200)
- // 40 W LED modeling light (brightness equivalent to a 300 W halogen light)
- // Sturdy metal housing with integrated tilt bracket, umbrella holder and handle
- // Changeable lamp cable (round plug) in 5 m, 7 m and 10 m length
Customized lengths available upon request (standard delivery with 90° round connector)
- // Changeable protection glass
- // Plug-in quartz glass flash tube
- // Modeling light on the head can be switched separately (on/off/time)
- // Large selection of quickly changeable Hensel EH light formers
- // Easy and safe operation
- // Smallest packing dimensions

TECHNICAL DATA

Connection: round plug
Modeling lamp: 40 W LED
Cooling fan: Yes
Reflector connection: EH (10 cm)
Cable length: 5 m
Multivoltage: Yes
Switch (on/off/time) for modeling lamp: Yes
Pluggable flash tube: Yes
Glass dome: Yes
Integrated umbrella holder with clamp: Yes
Weight (without cable): 1.75 kg
Dimensions (LxWxH) without cable: 19 x 12.5 x 16 cm

Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense.

The values can differ due to tolerances in used components.

Date of revision: October 2013

HENSEL
■■■■ PERFORMING LIGHT