//product info

// FLASH HEADS



EH MINI^{i}

Code no. 3635

// Sturdy metal housing with integrated tilt bracket, umbrella holder and handle
// Changeable lamp cable (round or long plug) in 5 m, 7 m and 10 m length Customized lengths available upon request (standard delivery with 90° round socket and round plug)
// Integrated micro controller to monitor operating condition and digital communication with Nova D and Nova DL
// Bright 650 W modeling light and changeable glass protector
// Plug-in silica glass flash tube
// Active cooling with quiet fan
// Up to 3000 Ws performance
// Can be used with all current Hensel flash generators (Tria 6000 S: can only be operated on the „3000" jacks)
// Large selection of quickly changeable Hensel EH light formers
// Multivoltage (110 V - 230 V)
// Easy and safe operation
// Smallest packing dimensions

TECHNICAL DATA

Output: 3000 J
Connection: 20-pin or round plug
Modeling lamp up to: 650 W
Cooling fan: Yes
Reflector connection: EH (10 cm)
Cable length: 5 m
Multivoltage: Yes
On/off switch for flash and modeling lamp: Yes
Pluggable flash tube: Yes
Glass dome: Yes
Integrated umbrella holder with clamp: Yes
Weight (incl. 5 m cable): 2,6 kg
Dimensions (LxWxH): 19 x 12 x 16 cm (without cable)

Technical data are subject to change. The listed values are guide values and should not be understood as binding in a legal sense. The values can differ due to tolerances in used components. Values attained at 230 V / 50 Hz voltage. Date of revision: May 2012

HENSEL
PERFORMING LIGHT

HENSEL-VISIT GmbH & Co. KG // Robert-Bunsen-Str. 3 // 97076 Würzburg // Germany
Phone: +49-931-27881-0 // Fax: +49-931-27881-50 // info@hensel.de // www.hensel.de